

SolarPak

by powerB(⚡)X[®]



SLP2200

3 in ONE

UPS / INVERTER / POWERSTATION



www.powerboxups.com

SPECIFICATIONS



	Model	SLP2200
GENERAL	Capacity	2240Wh
	Cell Chemistry	LiFePO ₄
	Single Cell Capacity	50Ah@3.2V/pcs
	Lifecycle	4000+ Cycles to 80% Capacity
	Indicator	APP / TFT Screen
	Storage Temp.	-4°F~140°F (-20°C~60°C)
	Operating Temp.	32°F~122°F (0°C~50°C)
	Material	ABS + PC / Metal
	Weight	22.5±0.5kg
	Dimensions	405*288*255mm
	Battery Management System	OVP,UVP,OC,SCP,OTP,UTP,etc.
	Solar Charge System	MPPT Charge Controller
INPUT	XT60	500W*2 Max (DC / Solar 12V~59V)
	AC	1500W Max (100V~120V@60Hz)
OUTPUT	AC	2000W Max (100V~120V@60Hz)
	USB-C #1	45W Max
	USB-C #2	100W Max
	USB-A	18W Max (5V~12V)
	DC 5525	120W (12V / 10A)
	Car Port	120W (12V / 10A)

Recharge time: 1.2 hours